

WELL LOG AND REPORT TO THE STATE
ENGINEER OF NEVADA

Log No. 1326
 Rec. 6/9 1950
 Well No. [Stamp]
 Permit No. [Stamp]
 Do not fill in

Owner: J.M. Sinsion & Sons Driller: Darelle Free
 Address: Springville Utah Address: Pioche Nevada Lic. No. 30
 Location of well: SE 1/4 NE 1/4 Sec. 7, T. 3 N 7 S, R. 70 E, in Lincoln County
 or: 6' N. End 1515' W. of 1/2 section corner
 Water will be used for: Connection on Highway Const. Total depth of well: 232 ft.
 Size of drilled hole: 10 in Weight of casing per linear foot: 12 lb.
 Thickness of casing: 12 Gauge Temp. of water:
 Diameter and length of casing: 10 in for 232 ft.
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)
 If flowing well give flow in c.f.s. or g.p.m. and pressure:
 If nonflowing well give depth of standing water from surface: 130 ft.
 If flowing well describe control works:
 (Type and size of valve, etc.)
 Date of commencement of well: April 21, 1950 Date of completion of well: May 5, 1950
 Type of well rig: Churndrill

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	25	25	Silt
25	60	35	Sand & Gravel
60	90	30	Sand, Clay
90	110	20	Stratified Hardpan
110	120	10	Cemented Gravel
120	155	35	Sandy Clay
155	225	70	Stratified Clay & Hardpan
225	232	7	Sand

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
 from 135 to 232 ft.

Other aquifers

First water at 135 feet.

Casing perforated
 from 135 to 232 ft.

Size of perforations
 1/8 by 12 in

